

Description

Fastener Length: 23/32", MS51862 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | MS5186236 |
| Minimum Qty (MOQ): | 50 |
| NSN: | 5305-00-149-8610 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS51862-36 Specifications

| | |
|--------------------------------------------|-----------------------------------------------|
| Fastener Length: | 0.719 Inches Minimum And 0.781 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.340 Inches Minimum And 0.385 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Nonmachine Nominal Thread Diameter: | 0.190 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Nondefinitive Spec/std Data: | Ab Type |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51862-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.