

## P/N MS51862-4

### **Description**

Fastener Length: 15/32

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS518624

Minimum Qty (MOQ): 100

NSN: 5305-00-455-0403

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N MS51862-4 Specifications

Fastener Length:	0.469 Inches Minimum And 0.531 Inches Maximum
Head Diameter:	0.195 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Features Provided:	Casehardened
Nonmachine Thread Style:	Gimlet Point (type A, Ab Or Ba)
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Nonmachine Nominal Thread Diameter:	0.112 Inches
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
Nondefinitive Spec/std Data:	Ab Type

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS51862-4">https://military-fasteners.com/screws/machine+screws/MS51862-4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.