

P/N MS51862-5

Description

Fastener Length: 21/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS518625

Minimum Qty (MOQ): 25 EA

NSN: 5305-00-455-0406

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS51862-5 Specifications

| Fastener Length: | 0.594 Inches Minimum And 0.656 Inches Maximum |
|------------------------------------------------|-------------------------------------------------------------|
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.195 Inches Minimum And 0.225 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Features Provided: | Casehardened |
| Nonmachine Thread Style: | Gimlet Point (type A, Ab Or Ba) |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Nonmachine Nominal Thread Diameter: | 0.112 Inches |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec All Treatment Responses Overall |
| Nondefinitive Spec/std Data: | Ab Type |

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS51862-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS51862-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS51862-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms51862-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms51862-5 and selecting the quantity you want then complete your order.