

Description

MS51922-17 Self-Locking Hexagon Nut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | MS5192217 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5310-00-087-4652 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



NO IMAGE
AVAILABLE

P/N MS51922-17 Specifications

| | |
|---|---|
| Thread Class: | 2b |
| Thread Direction: | Right-hand |
| Locking Feature: | Prevailing Torque With Nonmetallic Insert |
| Lubrication: | Dry Film Lubricant |
| Nut Style: | Hexagon |
| Nut Height: | 0.438 Inches Minimum And 0.468 Inches Maximum |
| End Item Identification: | Mrap-rg-33 Armored Utility Vehicle (auv) |
| Width Across Flats: | 0.551 Inches Minimum And 0.564 Inches Maximum |
| Temp Rating: | 250.0 Deg Fahrenheit Nominal |
| Thread Series: | Unc |
| Thread Quantity Per Inch: | 16 |
| Nominal Thread Size: | 0.375 Inches |
| Bearing Surface Type: | Chamfered Or Washer Faced |
| Bearing Surface Finish: | 125.0 Microinches |
| Material: | Plastic Polyamide Locking Insert |
| Material: | Steel Nut |
| Material Document And Classification: | Sae J995, Gr 5 Assn Std Single Material Response Nut |
| Surface Treatment: | Cadmium Overall Except Insert And Chromate Overall Except Insert |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall Except Insert |

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS51922-17 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.