

Description

MS51922-33 Self-locking Hexagon Nut

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS5192233
Minimum Qty (MOQ):	10
NSN:	5310-00-225-6993
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS51922-33 Specifications

Thread Class:	2b
Thread Direction:	Right-hand
Locking Feature:	Prevailing Torque With Nonmetallic Insert
Lubrication:	Dry Film Lubricant
Nut Style:	Hexagon
Nut Height:	0.579 Inches Minimum And 0.609 Inches Maximum
End Item Identification:	Torpedo, Mk-48; Generator, 15kw, Diesel, Military Standard Family; Missile, Tomahawk; Aircraft, (ac-130h, Mc-130h, Ec-130e, Hc-130); Nsn 4210-01-486-1035 Tfft (tactical Fire Fighting Truck);2320-01-097-0248,2320-01-097-0249,2320-01-100-7672,2320-01-097-0260,2320 -01-195-7641 Hemtt (heavy Expanded Mobility Tactical Trucks); Mrap Auv Rg-33
Width Across Flats:	0.736 Inches Minimum And 0.752 Inches Maximum
Temp Rating:	250.0 Deg Fahrenheit Nominal
Thread Series:	Unc
Thread Quantity Per Inch:	13
Nominal Thread Size:	0.500 Inches
Bearing Surface Type:	Chamfered Or Washer Faced
Bearing Surface Finish:	125.0 Microinches
Material:	Plastic Polyamide Locking Insert
Material:	Steel Nut
Material Document And Classification:	Sae J995, Gr 5 Assn Std Single Material Response Nut
Surface Treatment:	Cadmium And Chromate Overall Except Insert
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec Single Treatment Response Overall Except Insert

How to Order

Order this self-locking hexagon nut from our inventory online by visiting https://military-fasteners.com/nuts/self_locking+hexagon+nuts/MS51922-33 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.