

Description

length: 9/16, thread: 4-40, pan head, corrosion resistant steel, coarse thread, MS51957 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS51957120
Minimum Qty (MOQ):	100
NSN:	5305-00-234-9629
Schedule B:	7318.15.9000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51957-120 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.482 Inches Minimum And 0.562 Inches Maximum
Fastener Length:	0.532 Inches Minimum And 0.562 Inches Maximum
Head Style:	Pan
Head Diameter:	0.205 Inches Minimum And 0.219 Inches Maximum
Head Height:	0.070 Inches Minimum And 0.080 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Mil-f-14072 Finish E300 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas1635 Professional/Industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51957-120> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.