

# P/N MS51957-127

### **Description**

Fastener Length: 1-1/8", Thread: 8-32, Thread Length: 1-1/8", MS51957 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS51957127

Minimum Qty (MOQ): 100

NSN: 5305-00-402-5788

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS51957-127 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.001 Inches Minimum And 1.125 Inches Maximum
Fastener Length:	1.063 Inches Minimum And 1.125 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting Or Steel
Screw Material Document And Classification:	Qq-s-763,300 Series Fed Spec 1st Material Response Or 66,300 Series Fed Std 1st Material Response Or Comp 16-18 Or 18-8 Assn Std 2nd Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS51957-127">https://military-fasteners.com/screws/machine+screws/MS51957-127</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.