

P/N MS51957-128

Description

Fastener Length: 1-3/8", Thread: 8-32, Thread Length: 1-3/8", pan head

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS51957128

Minimum Qty (MOQ): 100

NSN: 5305-00-455-2575

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N MS51957-128 Specifications

Thursd Class	
Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.251 Inches Minimum And 1.375 Inches Maximum
Fastener Length:	1.313 Inches Minimum And 1.375 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Material Document And Classification:	Astm A582 Assn Std 1st Material Response Or Fed Std No. 66 Fed Std 2nd Material Response Or 16-18 Assn Std 3rd Material Response Or 18-8 Assn Std 4th Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type Or 9c Style

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS51957-128 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.