

**Description**

length: 5/16", thread: 4-40, pan head, corrosion resistant steel, coarse thread, black oxide coating, MS51957 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS5195714B                                |
| Minimum Qty (MOQ):      | 100                                       |
| NSN:                    | 5305-00-459-4687                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS51957-14B Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 2a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.231 Inches Minimum And 0.312 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 0.281 Inches Minimum And 0.312 Inches Maximum  |
| <b>Head Style:</b>  | Pan  |
| <b>Head Diameter:</b>                                       | 0.205 Inches Minimum And 0.219 Inches Maximum  |
| <b>Head Height:</b>   | 0.070 Inches Minimum And 0.080 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                             | 0.112 Inches   |
| <b>Thread Quantity Per Inch:</b>                            | 40   |
| <b>Minimum Tensile Strength:</b>                            | 80000 Pounds Per Square Inch   |
| <b>Screw Material:</b>                                      | Steel Corrosion Resisting Or Steel   |
| <b>Screw Material Document And Classification:</b>          | Qq-s-763,300 Series Fed Spec 1st Material Response Or 66,300 Series Fed Std 1st Material Response Or Comp 16-18 Or 18-8 Assn Std 2nd Material Response |
| <b>Screw Surface Treatment:</b>                             | Oxide  |
| <b>Screw Surface Treatment Document And Classification:</b> | Mil-c-13924 Cl 4 Mil Spec Single Treatment Response  |
| <b>Thread Series Designator:</b>                            | Unc  |
| <b>Nondefinitive Spec/std Data:</b>                         | 3 Type And 9c Style  |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51957-14B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.