

**Description**

length: 5/8", thread: 4-40, pan head, corrosion resistant steel, coarse thread, MS51957 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5195718
Minimum Qty (MOQ):	100
NSN:	5305-00-054-5652
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS51957-18 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.451 Inches Minimum And 0.625 Inches Maximum
<b>Fastener Length:</b>	0.625 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.205 Inches Minimum And 0.219 Inches Maximum
<b>Head Height:</b>	0.070 Inches Minimum And 0.080 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Thread Quantity Per Inch:</b>	40
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51957-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.