

**Description**

length: 1/4", thread: 2-56, pan head, corrosion resistant steel, coarse thread, MS51957 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS519573
Minimum Qty (MOQ):	100
NSN:	5305-00-054-5637
Schedule B:	7318.22.0000
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS51957-3 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.214 Inches Minimum And 0.250 Inches Maximum
<b>Fastener Length:</b>	0.219 Inches Minimum And 0.250 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.155 Inches Minimum And 0.167 Inches Maximum
<b>Head Height:</b>	0.053 Inches Minimum And 0.062 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Thread Quantity Per Inch:</b>	56
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51957-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.