

Description

length: 7/16", thread: 8-32, pan head, corrosion resistant steel, coarse thread, black oxide coating, MS51957 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5195744B
Minimum Qty (MOQ):	100
NSN:	5305-00-433-3741
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51957-44B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.407 Inches Minimum And 0.438 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting Or Steel
Screw Material Document And Classification:	Qq-s-763,300 Series Fed Spec 1st Material Response Or 66,300 Series Fed Std 1st Material Response Or Comp 16-18 Or 18-8 Assn Std 2nd Material Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51957-44B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.