

P/N MS51957-50B

Description

length: 1-1/4", thread: 8-32, pan head, black oxide coating, corrosion resistant steel, coarse thread, MS51957 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS5195750B

Minimum Qty (MOQ): 100

NSN: 5305-01-011-1698

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N MS51957-50B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.126 Inches Minimum And 1.250 Inches Maximum
Fastener Length:	1.188 Inches Minimum And 1.250 Inches Maximum
Head Style:	Pan
Head Diameter:	0.306 Inches Minimum And 0.322 Inches Maximum
Head Height:	0.105 Inches Minimum And 0.115 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.164 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 301 Or Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304l Or Steel Comp 303 Plus X Or Steel Comp 303se Or Steel Comp 304 Or Steel Comp 304l Or Steel Comp 305 Or Steel Comp 308 Or Steel Comp 309 Or Steel Comp 309s Or Steel Comp 310 Or Steel Comp 310s Or Steel Comp 314 Or Steel Comp 316 Or Steel Comp 316l Or Steel Comp 317 Or Steel Comp 321 Or Steel Comp 323 Or Steel Comp 324 Or Steel Comp 347 Or Steel Comp 348 Or Steel Comp 384 Or Steel Comp 385 Or Steel Comp T15
Screw Surface Treatment:	Oxide
Screw Surface Treatment Document And Classification:	t Mil-c-13924,cl 4 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 9c Style

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS51957-508 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.