

Description

Fastener Length: 1-", Thread: 10-24, Thread Length: 63/64", MS51957 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5195767
Minimum Qty (MOQ):	100
NSN:	5305-00-050-9233
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51957-67 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.917 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Rg-31 Mrap
lii End Item Identification:	Rg-31 Mrap; Medium Mine Protected Vehicle - Mmpv
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51957-67> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.