

**Description**

Fastener Length: 1", Thread: 1/4-20, Thread Length: 63/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5195783
Minimum Qty (MOQ):	25
NSN:	5305-00-071-1318
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS51957-83 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.900 Inches Minimum And 1.000 Inches Maximum
<b>Fastener Length:</b>	1.000 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.473 Inches Minimum And 0.492 Inches Maximum
<b>Head Height:</b>	0.162 Inches Minimum And 0.175 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	Stream (std. Tensioned Replenishment At Sea Method); Missile Systems, Nato Sea Sparrow; Support Equipment, B-52 Aircraft; Aircraft, ( Ac-130h, Mc; Mrap Cougar Ambulance
<b>End Item Identification:</b>	Stream (std. Tensioned Replenishment At Sea Method); Missile Systems, Nato Sea Sparrow; Support Equipment, B-52 Aircraft; Aircraft, ( Ac-130h, Mc; Mrap Cougar Ambulance; Mrap Buffalo Mk2a2
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51957-83> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.