

Description

Fastener Length: 1", Thread: 1/4-20, Thread Length: 63/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5195783
Minimum Qty (MOQ):	25
NSN:	5305-00-071-1318
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51957-83 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.900 Inches Minimum And 1.000 Inches Maximum
Fastener Length:	1.000 Inches Nominal
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	Stream (std. Tensioned Replenishment At Sea Method); Missile Systems, Nato Sea Sparrow; Support Equipment, B-52 Aircraft; Aircraft, (Ac-130h, Mc; Mrap Cougar Ambulance
End Item Identification:	Stream (std. Tensioned Replenishment At Sea Method); Missile Systems, Nato Sea Sparrow; Support Equipment, B-52 Aircraft; Aircraft, (Ac-130h, Mc; Mrap Cougar Ambulance; Mrap Buffalo Mk2a2
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51957-83> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.