

Description

Fastener Length: 1/4", Thread: 2-64, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS519583
Minimum Qty (MOQ):	145
NSN:	5305-00-057-0499
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS51958-3 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Fastener Length:	0.219 Inches Minimum And 0.250 Inches Maximum
Head Style:	Pan
Head Diameter:	0.155 Inches Minimum And 0.167 Inches Maximum
Head Height:	0.053 Inches Minimum And 0.062 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	64
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51958-3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.