

**Description**

length: 1-1/4", thread: 10-32, pan head, corrosion resistant steel, fine thread, black oxide coating

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5195868B
Minimum Qty (MOQ):	50
NSN:	5305-00-497-7426
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N MS51958-68B Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.126 Inches Minimum And 1.250 Inches Maximum
<b>Fastener Length:</b>	1.188 Inches Minimum And 1.250 Inches Maximum
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.373 Inches Maximum
<b>Head Height:</b>	0.122 Inches Minimum And 0.133 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Material Document And Classification:</b>	Qq-s-763,300 Series Fed Spec Single Material Response Or 66,300 Series Fed Std Single Material Response Or Comp 16-18 Or 18-8 Assn Std Single Material Response
<b>Thread Series Designator:</b>	Unf
<b>Nondefinitive Spec/std Data:</b>	3 Type And 9c Style

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51958-68B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.