

## P/N MS51958-68B

## **Description**

length: 1-1/4", thread: 10-32, pan head, corrosion resistant steel, fine thread, black oxide coating

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: MS5195868B

Minimum Qty (MOQ): 50

NSN: 5305-00-497-7426

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N MS51958-68B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.126 Inches Minimum And 1.250 Inches Maximum
Fastener Length:	1.188 Inches Minimum And 1.250 Inches Maximum
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Corrosion Resisting
Screw Material Document And	Qq-s-763,300 Series Fed Spec Single Material Response Or 66,300 Series Fed Std Single Material Response Or Comp 16-18 Or 18-8
Classification:	Assn Std Single Material Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 9c Style

### **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS51958-68B">https://military-fasteners.com/screws/machine+screws/MS51958-68B</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.