

Description

length: 1-3/4", thread: 10-32, pan head machine screw, corrosion resistant steel, fine thread

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5195870
Minimum Qty (MOQ):	50
NSN:	5305-00-059-3666
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51958-70 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.688 Inches Minimum And 1.750 Inches Maximum
Fastener Length:	1.750 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:communications Terminal, Satellite An/gsc-39(v)1; Test Station, Oq-290(v)msm; Support Equipment, B-1 Aircraft; Boilers, 1200 Psi; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Main Feed Pumps; Trainer, B-1b Aircraft; Support Equipment, B-52 Aircraft;I Aircraft, Awacs, E-3a; Fire Control System, Mk-92 (fcs)
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51958-70> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.