

Description

Fastener Length: 2-1/64", Thread: 10-32, Thread Length: 1-15/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5195871
Minimum Qty (MOQ):	50
NSN:	5305-00-059-3667
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51958-71 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	1.938 Inches Minimum And 2.000 Inches Maximum
Fastener Length:	2.000 Inches Nominal
Head Style:	Pan
Head Diameter:	0.357 Inches Minimum And 0.373 Inches Maximum
Head Height:	0.122 Inches Minimum And 0.133 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Stream (std. Tensioned Replenishment At Sea Method); Fire Control System, Mk 92 (fcs); Support Equipment, B-1 Aircraft; Repair Facility, Oa8991; Communications Terminal, Satellite An/gsc-39(v)1; Missile, Air-to-air, Phoenix (aim-54); Missile, Air Intercept, Sidewinder (aim-9); Ground Mobile Force Satellite Comm Term (an/tsc-85a)
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51958-71> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.