

Description

Fastener Length: 7/8", Thread: 1/4-28, Thread Length: 7/8", MS51958 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5195882
Minimum Qty (MOQ):	25
NSN:	5305-00-059-5432
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51958-82 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.804 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	0.875 Inches Nominal
Head Style:	Pan
Head Diameter:	0.473 Inches Minimum And 0.492 Inches Maximum
Head Height:	0.162 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
End Item Identification:	W/s:central Message Switch, An/tyc-39a; Close In Weapon System (ciws-phalanx); Support Equipment, B-1 Aircraft; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-52 Aircraft; Missile, Air Intercept, Sidewinder (aim-9); Airborne Mobile Dir Air Spt Ctl (2id),(02m Jul83)(an/uyq-3a); Missile, Air-to-air, Phoenix (aim-54); Missile, Tomahawk
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51958-82> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.