

## Description

Fastener Length: 7/8", Thread: 1/4-28, Thread Length: 7/8", MS51958 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	MS5195882
Minimum Qty (MOQ):	25
NSN:	5305-00-059-5432
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS51958-82 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.804 Inches Minimum And 0.875 Inches Maximum
<b>Fastener Length:</b>	0.875 Inches Nominal
<b>Head Style:</b>	Pan
<b>Head Diameter:</b>	0.473 Inches Minimum And 0.492 Inches Maximum
<b>Head Height:</b>	0.162 Inches Minimum And 0.175 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>End Item Identification:</b>	W/s:central Message Switch, An/tyc-39a; Close In Weapon System (ciws-phalanx); Support Equipment, B-1 Aircraft; Aircraft (ac-130h, Mc-130h, Ec-130e, Hc-130); Support Equipment, B-52 Aircraft; Missile, Air Intercept, Sidewinder (aim-9); Airborne Mobile Dir Air Spt Ctl (2id),(02m Jul83)(an/uyq-3a); Missile, Air-to-air, Phoenix (aim-54); Missile, Tomahawk
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
<b>Screw Material Document And Classification:</b>	66 Fed Std All Material Responses
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51958-82> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.