

**Description**

MS51959-109 Machine Screw

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |                                           |
|-------------------------|-------------------------------------------|
| SKU / Model:            | MS51959109                                |
| Minimum Qty (MOQ):      | 25                                        |
| NSN:                    | 5305-00-082-6734                          |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS51959-109 Specifications

|                                                             |                                                                                        |
|-------------------------------------------------------------|----------------------------------------------------------------------------------------|
| <b>Thread Class:</b>                                        | 2a                                                                                     |
| <b>Thread Direction:</b>                                    | Right-hand                                                                             |
| <b>Thread Length:</b>                                       | 0.625 Inches Minimum And 0.750 Inches Maximum                                          |
| <b>Fastener Length:</b>                                     | 0.750 Inches Nominal                                                                   |
| <b>Head Style:</b>                                          | Flat Countersunk                                                                       |
| <b>Head Diameter:</b>                                       | 0.685 Inches Minimum And 0.762 Inches Maximum                                          |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                                                                    |
| <b>Nominal Thread Diameter:</b>                             | 0.375 Inches                                                                           |
| <b>Thread Quantity Per Inch:</b>                            | 16                                                                                     |
| <b>Minimum Tensile Strength:</b>                            | 80000 Pounds Per Square Inch                                                           |
| <b>Countersink Angle:</b>                                   | 80.0 Degrees Minimum And 82.0 Degrees Maximum                                          |
| <b>Screw Material:</b>                                      | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 |
| <b>Screw Material Document And Classification:</b>          | 66 Fed Std All Material Responses                                                      |
| <b>Screw Surface Treatment:</b>                             | Passivate                                                                              |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response                                             |
| <b>Thread Series Designator:</b>                            | Unc                                                                                    |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51959-109> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.