

Description

Fastener Length: 5/16", Thread: 4-40, Thread Length: 15/64",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5195914B
Minimum Qty (MOQ):	100
NSN:	5305-00-455-2513
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51959-14B Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.164 Inches Minimum And 0.245 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.195 Inches Minimum And 0.225 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.112 Inches
Thread Quantity Per Inch:	40
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting Or Steel
Screw Material Document And Classification:	Qq-s-763,300 Series Fed Spec 1st Material Response Or 66,300 Series Fed Std 1st Material Response Or Comp 16-18 Or 18-8 Assn Std 2nd Material Response
Screw Surface Treatment:	Oxide
Screw Surface Treatment Document And Classification:	Mil-c-13924,cl 4 Mil Spec Single Treatment Response
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	3 Type And 2c Style
Departure From Cited Designator:	As Modified By Finish

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51959-14B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.