

Description

Fastener Length: 5/16", Thread: 8-32, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS5195942 |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-765-4252 |
| Schedule B: | 7318.15.2091 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS51959-42 Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.250 Inches Minimum And 0.312 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.292 Inches Minimum And 0.332 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.164 Inches |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316 |
| Screw Material Document And Classification: | 66 Fed Std All Material Responses |
| Screw Surface Treatment: | Passivate |
| Screw Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51959-42> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.