

Description

Fastener Length: 5/16", Thread: 2-56, Thread Length: 1/4", black oxide

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS519594B |
| Minimum Qty (MOQ): | 100 |
| NSN: | 5305-00-455-2498 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS51959-4B Specifications

| | |
|---|--|
| Thread Class: | 2a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.194 Inches Minimum And 0.261 Inches Maximum |
| Fastener Length: | 0.281 Inches Minimum And 0.312 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.147 Inches Minimum And 0.172 Inches Maximum |
| Internal Drive Style: | Cross Recess Type 1 |
| Nominal Thread Diameter: | 0.086 Inches |
| Thread Quantity Per Inch: | 56 |
| Minimum Tensile Strength: | 80000 Pounds Per Square Inch |
| Countersink Angle: | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| Screw Material: | Steel Corrosion Resisting Or Steel |
| Screw Material Document And Classification: | Qq-s-763,300 Series Fed Spec 1st Material Response Or 66,300 Series Fed Std 1st Material Response Or Comp 16-18 Or 18-8 Assn Std 2nd Material Response |
| Screw Surface Treatment: | Oxide |
| Screw Surface Treatment Document And Classification: | Mil-c-13924,cl 4 Mil Spec Single Treatment Response |
| Thread Series Designator: | Unc |
| Nondefinitive Spec/std Data: | 3 Type And 2c Style |
| Departure From Cited Designator: | As Modified By Finish |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51959-4B> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.