

## Description


Fastener Length: 63/64", Thread: 1/4-18, Thread Length: 3/4",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS5195998                                 |
| Minimum Qty (MOQ):      | 50  |
| NSN:                    | 5305-00-763-7830                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



\* See page 2 for technical characteristics

## P/N MS51959-98 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 2a  |
| <b>Thread Direction:</b>                                    | Right-hand                                    |
| <b>Thread Length:</b>                                       | 0.809 Inches Minimum                          |
| <b>Fastener Length:</b>                                     | 0.969 Inches Minimum And 1.000 Inches Maximum |
| <b>Head Style:</b>  | Flat Countersunk                              |
| <b>Head Diameter:</b>                                       | 0.568 Inches Minimum And 0.635 Inches Maximum |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1                           |
| <b>Nominal Thread Diameter:</b>                             | 0.312 Inches                                  |
| <b>Thread Quantity Per Inch:</b>                            | 18  |
| <b>Minimum Tensile Strength:</b>                            | 80000 Pounds Per Square Inch                  |
| <b>Countersink Angle:</b>                                   | 80.0 Degrees Minimum And 82.0 Degrees Maximum |
| <b>Screw Material:</b>                                      | Steel Corrosion Resisting                     |
| <b>Screw Material Document And Classification:</b>          | 66 Fed Std Single Material Response           |
| <b>Screw Surface Treatment:</b>                             | Passivate                                     |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response    |
| <b>Thread Series Designator:</b>                            | Unc   |

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51959-98> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.