

**Description**

Fastener Length: 1-3/16", Thread: 5/16-24, Thread Length: 0-59/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |  |
|-------------------------|--|
| SKU / Model:            | MS51960102                                 |
| Minimum Qty (MOQ):      | 5 EA                                       |
| NSN:                    | 5305-00-425-2172                           |
| Schedule B:             | 7318.15.6080                               |
| ECCN:                   | EAR99                                      |
| National Motor Freight: | 096630, Screws Noi Brass / Bronze / Copper |

NO IMAGE  
AVAILABLE

## P/N MS51960-102 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 2a  |
| <b>Thread Direction:</b>                                    | Right-hand  |
| <b>Thread Length:</b>                                       | 0.914 Inches Minimum And 1.059 Inches Maximum   |
| <b>Fastener Length:</b>                                     | 1.188 Inches Minimum And 1.250 Inches Maximum   |
| <b>Head Style:</b>  | Flat Countersunk  |
| <b>Head Diameter:</b>                                       | 0.568 Inches Minimum And 0.635 Inches Maximum   |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1   |
| <b>Nominal Thread Diameter:</b>                             | 0.312 Inches  |
| <b>Thread Quantity Per Inch:</b>                            | 24  |
| <b>Minimum Tensile Strength:</b>                            | 80000 Pounds Per Square Inch  |
| <b>Countersink Angle:</b>                                   | 80.0 Degrees Minimum And 82.0 Degrees Maximum   |
| <b>Screw Material:</b>                                      | Steel Corrosion Resisting   |
| <b>Screw Material Document And Classification:</b>          | Qq-s-763,300 Series Fed Spec Single Material Response Or 66,300 Series Fed Std Single Material Response Or Comp 16-18 Or 18-8 Assn Std Single Material Response |
| <b>Screw Surface Treatment:</b>                             | Passivate   |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response  |
| <b>Thread Series Designator:</b>                            | Unf   |
| <b>Nondefinitive Spec/std Data:</b>                         | 3 Type And 2c Style   |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51960-102> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.