

Description

Fastener Length: 0-63/64", Thread: 8-32, Thread Length: 7/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5196049
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-774-9620
Schedule B:	7318.15.6080
ECCN:	9A991



\* See page 2 for technical characteristics

## P/N MS51960-49 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.900 Inches Minimum
<b>Fastener Length:</b>	0.969 Inches Minimum And 1.000 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.292 Inches Minimum And 0.332 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Countersink Angle:</b>	80.0 Degrees Minimum And 82.0 Degrees Maximum
<b>Screw Material:</b>	Steel Corrosion Resisting
<b>Screw Material Document And Classification:</b>	66 Fed Std Single Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51960-49> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.