

Description


Fastener Length: 5/16", Thread: 10-32, Thread Length: 5/16",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5196062
Minimum Qty (MOQ):	100
NSN:	5305-00-059-5433
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51960-62 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Minimum And 0.312 Inches Maximum
Fastener Length:	0.281 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.340 Inches Minimum And 0.385 Inches Maximum
Head Height:	0.068 Inches Minimum And 0.081 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51960-62> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.