

## P/N MS51960-64

## **Description**

Fastener Length: 7/16", Thread: 10-32, Thread Length: 7/16

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

### Order this part online

#### **Additional Information**

SKU / Model: MS5196064

Minimum Qty (MOQ): 100

NSN: 5305-00-071-1321

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N MS51960-64 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.376 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	0.438 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.340 Inches Minimum And 0.385 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	80.0 Degrees Minimum And 82.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 304 Or Steel Comp 305 Or Steel Comp 316
Screw Material Document And Classification:	66 Fed Std All Material Responses
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf

## **How to Order**

Order this machine screw from our inventory online by visiting <a href="https://military-fasteners.com/screws/machine+screws/MS51960-64">https://military-fasteners.com/screws/machine+screws/MS51960-64</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.