

**Description**

Fastener Length: 5/16", Thread: 1/4-28, Thread Length: 7/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | MS5196079                                 |
| Minimum Qty (MOQ):      | 20 EA                                     |
| NSN:                    | 5305-01-019-2397                          |
| Schedule B:             | 7318.15.6080                              |
| ECCN:                   | 9A991                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N MS51960-79 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 2a   |
| <b>Thread Direction:</b>                                    | Right-hand   |
| <b>Thread Length:</b>                                       | 0.102 Inches Minimum And 0.220 Inches Maximum  |
| <b>Fastener Length:</b>                                     | 0.280 Inches Minimum And 0.312 Inches Maximum  |
| <b>Head Style:</b>  | Flat Countersunk Undercut  |
| <b>Head Diameter:</b>                                       | 0.452 Inches Minimum And 0.507 Inches Maximum  |
| <b>Head Height:</b>   | 0.092 Inches Minimum And 0.107 Inches Maximum  |
| <b>Internal Drive Style:</b>                                | Cross Recess Type 1  |
| <b>Nominal Thread Diameter:</b>                             | 0.250 Inches   |
| <b>Thread Quantity Per Inch:</b>                            | 28   |
| <b>Minimum Tensile Strength:</b>                            | 80000 Pounds Per Square Inch   |
| <b>Countersink Angle:</b>                                   | 82.0 Degrees Nominal   |
| <b>Screw Material:</b>                                      | Steel Comp 304 Or Steel Comp 301   |
| <b>Screw Material Document And Classification:</b>          | Qq-s-763 Fed Spec 1st Material Response Or Fed Std 66 Fed Spec 2nd Material Response |
| <b>Screw Surface Treatment:</b>                             | Passivate  |
| <b>Screw Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response   |
| <b>Thread Series Designator:</b>                            | Unf  |
| <b>Nondefinitive Spec/std Data:</b>                         | 3 Type And 2c Style  |

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51960-79> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.