



Military-Fasteners.com

P/N MS51960-79

Description

Fastener Length: 5/16", Thread: 1/4-28, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5196079
Minimum Qty (MOQ):	20 EA
NSN:	5305-01-019-2397
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51960-79 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.102 Inches Minimum And 0.220 Inches Maximum
Fastener Length:	0.280 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.452 Inches Minimum And 0.507 Inches Maximum
Head Height:	0.092 Inches Minimum And 0.107 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.250 Inches
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	82.0 Degrees Nominal
Screw Material:	Steel Comp 304 Or Steel Comp 301
Screw Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Or Fed Std 66 Fed Spec 2nd Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	3 Type And 2c Style

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51960-79> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.