

P/N MS51963-170

Description

Fastener Length: 3/4", Thread: 3/4-10, Head Width: 3/8", Thread Length: 3/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: MS51963170

Minimum Qty (MOQ): 5 EA

NSN: 5305-00-725-0194

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N MS51963-170 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Fastener Length:	0.735 Inches Minimum And 0.765 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.750 Inches
Width Across Flats:	0.375 Inches Nominal
Thread Quantity Per Inch:	10
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4032 Overall Or Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	66 Fed Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
Thread Series Designator:	Unc
Nondefinitive Spec/std Data:	1 Type And 4 Style

How to Order

Order this set screw from our inventory online by visiting https://military-fasteners.com/screws/setscrews/MS51963-170 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.