

Description


MS51964-121 Setscrew

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|-------------------------------------------|
| SKU / Model: | MS51964121 |
| Minimum Qty (MOQ): | 10 |
| NSN: | 5305-01-025-9979 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N MS51964-121 Specifications

| | |
|-------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Fastener Length: | 0.178 Inches Minimum And 0.198 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Point Style: | Cup |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Width Across Flats: | 0.094 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall |
| Material Document And Classification: | 66 Fed Std All Material Responses Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 1 Type And 4 Style |

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS51964-121> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.