

Description

Fastener Length: 47/64", Thread: 10-32, Head Width: 3/32", Thread Length: 47/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS51964129
Minimum Qty (MOQ):	15 EA
NSN:	5305-01-119-5037
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N MS51964-129 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.730 Inches Minimum And 0.770 Inches Maximum
Fastener Length:	0.730 Inches Minimum And 0.770 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Cup
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.190 Inches
Width Across Flats:	0.094 Inches Nominal
Thread Quantity Per Inch:	32
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Type2 Class 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 4 Style

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS51964-129> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.