

Description

Fastener Length: 1/8", Thread: 8-32, Head Width: 5/64", Thread Length: 1/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS51965131
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-212-8184
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS51965-131 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.115 Inches Minimum And 0.135 Inches Maximum
<b>Fastener Length:</b>	0.115 Inches Minimum And 0.135 Inches Maximum
<b>Head Style:</b>	Headless (setscrew)
<b>Locking Feature:</b>	Patch Threads Or Pellet Threads Or Strip Threads
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.164 Inches
<b>Width Across Flats:</b>	0.078 Inches Nominal
<b>Thread Quantity Per Inch:</b>	32
<b>Hardness Rating:</b>	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Type 2 Class 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc
<b>Nondefinitive Spec/std Data:</b>	1 Type And 1 Style

## How to Order

Order this set screw from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS51965-131> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.