

Description


Fastener Length: 3/16", Thread: 4-40, Head Width: 1/16", Thread Length: 3/16

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS519659
Minimum Qty (MOQ):	20
NSN:	5305-00-724-6778
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N MS51965-9 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.188 Inches Maximum
<b>Fastener Length:</b>	0.188 Inches Nominal
<b>Head Style:</b>	Headless (setscrew)
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.112 Inches
<b>Width Across Flats:</b>	0.050 Inches Nominal
<b>Thread Quantity Per Inch:</b>	40
<b>Hardness Rating:</b>	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS51965-9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.