

Description

Fastener Length: 3/8", Thread: 10-32, Head Width: 3/32", Thread Length: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS51966114 |
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-128-4079 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS51966-114 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Fastener Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Point Style: | Flat |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Width Across Flats: | 0.094 Inches Nominal |
| Thread Quantity Per Inch: | 32 |
| Hardness Rating: | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type 2 Class 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 1 Type And 1 Style |

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS51966-114> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.