

P/N MS51966-147

Description

Fastener Length: 1/2", Thread: 3/8-24, Head Width: 3/16", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order EREE of charge

Order this part online

Additional Information

SKU / Model: MS51966147

Minimum Qty (MOQ): 10 EA

NSN: 5305-01-081-5043

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)

NO IMAGE AVAILABLE

^{*} See page 2 for technical characteristics

P/N MS51966-147 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Fastener Length:	0.490 Inches Minimum And 0.510 Inches Maximum
Head Style:	Headless (setscrew)
Locking Feature:	Patch Threads Or Pellet Threads Or Strip Threads
Point Style:	Flat
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.375 Inches
Width Across Flats:	0.188 Inches Nominal
Thread Quantity Per Inch:	24
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unf
Nondefinitive Spec/std Data:	1 Type And 1 Style

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/MS51966-147 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS51966-147 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/machine+screws/MS51966-147 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/screws/ms51966-147 and selecting the quantity you want of the complete your order.