

P/N MS51966-147

Military-Fasteners.com

Description

Fastener Length: 1/2", Thread: 3/8-24, Head Width: 3/16", Thread Length: 1/2"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | MS51966147 |
|-------------------------|---|
| Minimum Qty (MOQ): | 10 EA |
| NSN: | 5305-01-081-5043 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N MS51966-147 Specifications

| Thread Class: | За |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Fastener Length: | 0.490 Inches Minimum And 0.510 Inches Maximum |
| Head Style: | Headless (setscrew) |
| Locking Feature: | Patch Threads Or Pellet Threads Or Strip Threads |
| Point Style: | Flat |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.375 Inches |
| Width Across Flats: | 0.188 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Hardness Rating: | 45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unf |
| Nondefinitive Spec/std Data: | 1 Type And 1 Style |

How to Order

Order this screw from our inventory online by visiting <u>https://military-fasteners.com/screws/machine+screws/MS51966-147</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.