

**Description**

Fastener Length: 0-1/1", Thread: 1/4-28, Head Width: 1/8", Thread Length: 0-1/1"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5196667
Minimum Qty (MOQ):	20 EA
NSN:	5305-00-728-6331
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS51966-67 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.985 Inches Minimum And 1.015 Inches Maximum
<b>Fastener Length:</b>	0.985 Inches Minimum And 1.015 Inches Maximum
<b>Head Style:</b>	Headless (setscrew)
<b>Point Style:</b>	Flat
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Width Across Flats:</b>	0.125 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Hardness Rating:</b>	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
<b>Material:</b>	Steel Comp 4032 Overall Or Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
<b>Material Document And Classification:</b>	66 Fed Std All Material Responses Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,type 2,class 3 Fed Spec All Treatment Responses Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51966-67> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.