



Military-Fasteners.com

P/N MS51973-8

Description

Fastener Length: 1/8", Thread: 4-40, Head Width: 1/16", Thread Length: 1/8"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS519738
Minimum Qty (MOQ):	15 EA
NSN:	5305-00-051-4483
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N MS51973-8 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Fastener Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Head Style:	Headless (setscrew)
Point Style:	Cone
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.112 Inches
Width Across Flats:	0.050 Inches Nominal
Thread Quantity Per Inch:	40
Hardness Rating:	45.0 Rockwell C Minimum Overall And 53.0 Rockwell C Maximum Overall
Material:	Steel Comp 4032 Overall Or Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
Material Document And Classification:	Aisi Assn Std All Material Responses Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this setscrew from our inventory online by visiting <https://military-fasteners.com/screws/setscrews/MS51973-8> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.