

**Description**

Fastener Length: 55/64", Thread: 10-24, Head Width: 1/8", Thread Length: 23/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS519752
Minimum Qty (MOQ):	5
NSN:	5305-00-949-6184
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS51975-2 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.355 Inches Minimum And 0.375 Inches Maximum
<b>Fastener Length:</b>	0.860 Inches Minimum And 0.870 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.357 Inches Minimum And 0.375 Inches Maximum
<b>Head Height:</b>	0.177 Inches Minimum And 0.187 Inches Maximum
<b>Shoulder Diameter:</b>	0.246 Inches Minimum First Shoulder And 0.248 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.495 Inches Minimum First Shoulder And 0.505 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Width Across Flats:</b>	0.125 Inches Nominal
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	140000 Pounds Per Square Inch
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51975-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.