

Description

Fastener Length: 55/64", Thread: 10-24, Head Width: 1/8", Thread Length: 23/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | MS519752 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5305-00-949-6184 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N MS51975-2 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.355 Inches Minimum And 0.375 Inches Maximum |
| Fastener Length: | 0.860 Inches Minimum And 0.870 Inches Maximum |
| Head Style: | Flat Chamfer |
| Head Diameter: | 0.357 Inches Minimum And 0.375 Inches Maximum |
| Head Height: | 0.177 Inches Minimum And 0.187 Inches Maximum |
| Shoulder Diameter: | 0.246 Inches Minimum First Shoulder And 0.248 Inches Maximum First Shoulder |
| Shoulder Length: | 0.495 Inches Minimum First Shoulder And 0.505 Inches Maximum First Shoulder |
| Internal Drive Style: | Hexagon |
| Nominal Thread Diameter: | 0.190 Inches |
| Width Across Flats: | 0.125 Inches Nominal |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 140000 Pounds Per Square Inch |
| Hardness Rating: | 32.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall |
| Shoulder Shape: | Round First Shoulder |
| Material: | Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall |
| Surface Treatment: | Cadmium Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unc |

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51975-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.