

Description

MS51975-24 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	MS5197524
Minimum Qty (MOQ):	5
NSN:	5305-00-415-2148
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



NO IMAGE
AVAILABLE

P/N MS51975-24 Specifications

Thread Class:	3a
Thread Length:	0.480 Inches Minimum And 0.500 Inches Maximum
Fastener Length:	2.735 Inches Minimum And 2.745 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.543 Inches Minimum And 0.562 Inches Maximum
Head Height:	0.240 Inches Minimum And 0.250 Inches Maximum
Shoulder Length:	2.245 Inches Minimum First Shoulder And 2.255 Inches Maximum First Shoulder
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.312 Inches
Width Across Flats:	0.188 Inches Nominal
Thread Quantity Per Inch:	18
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Thread Series Designator:	Unc

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51975-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.