

**Description**

Fastener Length: 2-11/32", Thread: 3/8-16, Head Width: 1/4", Thread Length: 39/64", MS51975 series screw

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	MS5197532
Minimum Qty (MOQ):	5
NSN:	5305-00-941-9426
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N MS51975-32 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.595 Inches Minimum And 0.625 Inches Maximum
<b>Fastener Length:</b>	2.340 Inches Minimum And 2.380 Inches Maximum
<b>Head Style:</b>	Flat Chamfer
<b>Head Diameter:</b>	0.729 Inches Minimum And 0.750 Inches Maximum
<b>Head Height:</b>	0.302 Inches Minimum And 0.312 Inches Maximum
<b>Shoulder Diameter:</b>	0.496 Inches Minimum First Shoulder And 0.498 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	1.745 Inches Minimum First Shoulder And 1.755 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	Hexagon
<b>Nominal Thread Diameter:</b>	0.375 Inches
<b>Width Across Flats:</b>	0.250 Inches Nominal
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	140000 Pounds Per Square Inch
<b>Hardness Rating:</b>	32.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Material:</b>	Steel Comp 4037 Overall Or Steel Comp 4137 Overall Or Steel Comp 4140 Overall Or Steel Comp 8630 Overall Or Steel Comp 8740 Overall
<b>Surface Treatment:</b>	Cadmium Overall And Chromate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Ty2cl 3 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51975-32> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.