

Description

Fastener Length: 3-55/64", Thread: 5/8-11, Head Width: 3/8", Thread Length: 55/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	MS5197559
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-159-2786
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N MS51975-59 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.845 Inches Minimum And 0.875 Inches Maximum
Fastener Length:	3.845 Inches Minimum And 3.875 Inches Maximum
Head Style:	Flat Chamfer
Head Diameter:	0.977 Inches Minimum And 1.000 Inches Maximum
Head Height:	0.490 Inches Minimum And 0.500 Inches Maximum
Shoulder Diameter:	0.746 Inches Minimum First Shoulder And 0.748 Inches Maximum First Shoulder
Shoulder Length:	3.000 Inches Nominal First Shoulder
Single Shear Strength:	16600 Pounds Per Square Inch
Internal Drive Style:	Hexagon
Nominal Thread Diameter:	0.625 Inches
Width Across Flats:	0.375 Inches Nominal
Thread Quantity Per Inch:	11
Minimum Tensile Strength:	140000 Pounds Per Square Inch
Hardness Rating:	32.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall
Shoulder Shape:	Round First Shoulder
Material:	Steel Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416,ty 2,cl 3 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/MS51975-59> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.