

Description

Height: 9/64", serrated, MS51990 series ring

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|-----------------------------|
| SKU / Model: | MS51990E107P |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5365-01-008-9632 |
| ECCN: | EAR99 |
| National Motor Freight: | 095190, Hardware, Noi Sub 9 |



P/N MS51990E107P Specifications

| | |
|---|---|
| Inside Diameter: | 0.387 Inches Minimum And 0.594 Inches Maximum |
| Pilot Diameter: | 0.480 Inches Nominal |
| Overall Height: | 0.145 Inches Nominal |
| Overall Outside Diameter: | 0.541 Inches Minimum And 0.550 Inches Maximum |
| Inner Serration Quantity: | 24 |
| Side Outer Serrations Omitted For Close Edge Installation: | Two Sides |
| Material: | Cres A-286 Ams5734 |
| Material: | Cres A-286 Ams5734 |
| Surface Treatment: | Passivated Per Qq-p-35 |
| Surface Treatment: | Passivated Per Qq-p-35 |

How to Order

Order this lock ring from our inventory online by visiting <https://military-fasteners.com/rings/retaining+rings/MS51990E107P> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.